



# AGRIPLUS(F-2)

## Tractor in Field and Haulage

- ✓ Excellent Steering Control: Strong 3-rib pattern with a wider centre rib ensures better steering control and smooth maneuverability on field and road
- ✓ Higher Puncture Protection: Advanced groove design with extra under-tread and a tough cut-resistant compound ensures superior defense against thorn and stubble punctures
- ✓ Durability & Longevity: Reinforced carcass and advanced tread compound deliver longer tread life and exceptional durability in both farm and haulage operations

### Application



## TECHNICAL SPECIFICATIONS

Tyre Size	PR	TT/TL	LI/SS	Recomm. Rim	Alternate Rim	Unloaded Inflated Dimension		Static Loaded Radius	Rolling Circumference	Max Speed	Load Carrying Capacity (Max Load)	Inflation Pressure
						SW	OD					
						mm	mm	mm	mm	km/h	kg	bar
6.00-16	8	TT	94 A6	4.50E	4.00E, 5.00F	175	758	348	2267	30	670	4.7
6.50-16	8	TT	98 A6	4.50E	4.00E, 5.00F, 5.50F	186	784	359	2345	30	750	4.2
7.50-16	8	TT	103 A6	5.50F	5.00F, 6.00F	210	815	372	2437	30	875	3.7