



AGRILEAP T40 (F-2)

- Unique T Lug with Center Rib Design:**
 Ensures excellent steering performance and ride comfort in both on-road and off-road applications. Used in Soil Tillage and Haulage applications.
- Higher Tread Depth:** Higher mileage. Longer Tyre life.
- Advance Tread compound:** Engineered for robust cut and tear resistance on all surfaces, maximizing service longevity.
- Optimized Tread Groove Design:** Designed for effective self-cleaning, reducing mud retention and ensuring reliable traction.
- Strong Nylon Casing:** Heavy load-carrying capacity. Resistance to Impact Failure.

Application



TECHNICAL SPECIFICATIONS

Tyre Size	PR	TT/TL	LI/SS	Recomm. Rim	Alternate Rim	Unloaded Inflated Dimension		Static Loaded Radius	Rolling Circumference	Max Speed	Load Carrying Capacity	
						SW (mm)	OD (mm)				(Max Load) (kg)	Inflation Pressure (bar)
						(in)	(in)	(in)	(in)	(km/h)	(lbs)	(psi)
8.00-16	8	TT	105 A6	5.50F	-	211	835	380	2497	30	925	3.6
						8.3	32.9	15.0	98.3	19	2040	52
9.00-16	10	TT	115 A6	W8	W7,6.50F	254	862	391	2578	30	1215	4.15
						10.0	33.9	15.4	101.5	19	2680	60
10.00-16	10	TT	118 A6	W8	-	280	905	409	2707	30	1320	3.4
						11.0	35.6	16.1	106.6	19	2910	49
11.00-16	10	TT	121 A6	W10L	W8L,8LB,10LB	326	970	436	2901	30	1450	3.3
						12.8	38.2	17.2	114.2	19	3200	48