



GRADER MAX

Premium Grader Tyre

- ✓ Robust cut resistant tread compound
- ✓ Superior casing strength to resist impact damage
- ✓ Reliable under extreme service conditions

TECHNICAL SPECIFICATIONS

Size	Type (TT / TL)	Ply Rating	TRA Code	Rim Rec.	Sectional Width (mm)	Overall Diameter (mm)	Rolling Cir. (mm)	Static Loaded Radius (mm)	Speed Radius Index	Load Index	Speed Symbol	Load range (kg)	Inflation Pressure (psi)	Tube Valve Code
13.00-24	TT	12	G-2/L-2	8.00TG SDC	338	1290	3858	586	625	--	--	2725 @ 40 kmph 5600 @ 10 kmph	44 65	TR 220A
13.00-24	TL	16	G-2/L-2	8.00TG SDC	338	1290	3858	586	625	--	--	3250 @ 40 kmph 6500 @ 10 kmph	65 87	--
14.00-24	TT	12	G-2/L-2	8.00TG SDC	365	1345	4023	609	650	--	--	3075 @ 40 kmph 6300 @ 10 kmph	40 62	TR 220A
14.00-24	TL	16	G-2/L-2	8.00TG SDC	365	1345	4023	609	650	--	--	3650 @ 40 kmph 7300 @ 10 kmph	54 80	--