



SHAN+

Durable - Tractor Tyre

- ✓ Superior lug design ensures maximum traction
- ✓ Cut resistant tread compound ensures reduced stubble penetration
- ✓ Suitable for both haulage & agriculture
- ✓ Better tyre floatation & less soil compaction
- ✓ Smooth channel for self cleaning

Application



TECHNICAL SPECIFICATIONS

Size	Type (TT / TL)	Ply Rating	TRA Code	Rim Rec.	Sectional Width (mm)	Overall Diameter (mm)	Rolling Cir. (mm)	Static Loaded Radius (mm)	Speed Radius Index	Load Index	Speed Symbol	Load range (kg)	Inflation Pressure (psi)	Tube Valve Code
12.4-28	TT	12	R-1	W11	328	1284	3840	592	600	125	A6	1650	36	TR 218A
13.6-28	TT	12	R-1	W12	355	1341	4011	616	650	128	A6	1800	33	TR 218A
14.9-28	TT	12	R-1	W13	386	1386	4145	634	650	134	A6	2120	33	TR 218A
16.9-28	TT	12	R-1	W 15L	446	1437	4298	655	675	143	A6	2725	35	TR 218A
16.9-30	TT	10	R-1	W 15L	448	1490	4456	682	700	140	A6	2500	30	TR 218A
18.4-30	TT	14	R-1	W 15L	492	1580	4725	719	750	151	A6	3450	37	TR 218A