



ULTRA GRIP

Premium Loader Tyre

- ✓ Unique tread design for higher grip
- ✓ Stronger carcass to prevent impact failure
- ✓ Cut & chip resistant tread compound for on/off application
- ✓ Trouble free under severe service conditions

TECHNICAL SPECIFICATIONS

Size	Type (TT / TL)	Ply Rating	TRA Code	Rim Rec.	Sectional Width (mm)	Overall Diameter (mm)	Rolling Cir. (mm)	Static Loaded Radius (mm)	Speed Radius Index	Load Index	Speed Symbol	Load range (kg)	Inflation Pressure (psi)	Tube Valve Code
14.00-25	TT	20	E-3/L-3	10.00/1.5	384	1368	4091	620	650	--	--	4625 @ 50 kmph 8500 @10 kmph	69 102	TRJ 1175
17.5-25	TL	20	E-3/L-3	14.00/1.5	443	1381	4130	625	650	--	--	5000 @50 kmph 8250 @10 kmph	58 83	--
20.5-25	TL	20	E-3/L-3	17.00/3.0	530	1505	4501	676	725	--	--	6000 @50 kmph 9500 @10 kmph	47 65	--
23.5-25	TL	20	E-3/L-3	19.50/2.5	610	1620	4845	724	775	--	--	7300 @50 kmph 10900 @10 kmph	44 54	--



TECHNICAL SPECIFICATIONS

Size	Type (TT / TL)	Ply Rating	TRA Code	Rim Rec.	Sectional Width (mm)	Overall Diameter (mm)	Rolling Cir. (mm)	Static Loaded Radius (mm)	Speed Radius Index	Load Index	Speed Symbol	Load range (kg)	Inflation Pressure (psi)	Tube Valve Code
14.00-25	TT	24	E-3/L-3	10.00/1.5	384	1368	4091	620	650	--	--	5150 @ 50 kmph 9500 @10 kmph	83 123	TRJ 1175
20.5-25	TL	24	E-3/L-3	17.00/3.0	530	1505	4501	676	725	--	--	6700 @50 kmph 10300 @10 kmph	58 76	--
23.5-25	TL	24	E-3/L-3	19.50/2.5	610	1620	4845	724	775	--	--	8000 @50 kmph 12500 @10 kmph	51 69	--
26.5-25	TL	28	E-3/L-3	22.00/3.0	715	1725	5159	767	825	--	--	10000 @50 kmph 15500 @10 kmph	51 69	--
29.5-25	TL	28	E-3/L-3	25.00/3.5	785	1885	5638	833	900	--	--	11500 @50 kmph 17500 @10 kmph	47 62	--
26.5-25	TL	32	E-3/L-3	22.00/3.0	715	1725	5159	767	825	--	--	11200 @50 kmph 17000 @10 kmph	62 80	--
29.5-25	TL	34	L-3	25.00/3.5	785	1885	5638	833	900	--	--	19800 @ 10 kmph	78	--